

CARE AND MAINTENANCE INSTRUCTIONS HARLEQUIN ROCKSURE

Entrance Matting

The first line of defence in protecting your flooring is to have effective barrier mats at the entrance to any floorings. An effective matting will significantly reduce the amount of wet and dry soiling being carried on the underside of footwear.

To be effective we would strongly recommend the length of the matting should be at least 2 to 3 footfalls, and it should be regularly vacuumed and cleaned. Limiting foot borne contamination will make your daily maintenance regime easier.

The recommended maintenance instructions must be adhered to so as to ensure that the floor covering retains its appearance for longer and most importantly does not impair its performance and aesthetics.

Initial Maintenance / New Installation

Sweep the floor covering with a soft broom or dust control microfibre mop to remove any loose dirt, debris and dust.

Using a spray bottle filled with the matte floor polish, lightly spray across the floor, avoiding saturation of the floor. Follow up by mop wiping the floor.

Allow the floor to dry thoroughly before use.

Daily Maintenance

Sweep the floor covering with a soft broom or dust control microfibre mop to remove any loose dirt, debris and dust.

If required, damp mop the floor using a diluted solution of Harlequin Vinyl Daily Floor Cleaner in the ratio of 1:50, 100 ml of Daily Floor Cleaner in 5 litres of warm water.

Follow up by rinsing the floor with a damp, not wet mop. Avoid saturation of the floor. Allow the floor to dry before use.

Monthly Maintenance

Sweep the floor covering with a soft broom or dust control microfibre mop to remove any loose dirt, debris and dust.

It is advisable that on a monthly basis, the floor should be treated by spray cleaning it with the matte floor polish to restore the appearance of the product.

Using a spray bottle filled with the matte floor polish, lightly spray across the floor, avoiding saturation of the floor. Follow up by mop wiping the floor.

Allow the floor to dry thoroughly before use.

Document Number: CM RS

Issue 2

0325

LONDON LUXEMBOURG BERLIN PARIS MADRID LOS ANGELES PHILADELPHIA FORT WORTH SYDNEY HONG KONG TOKYO

Company Reg No. 1420396. Registered in England and Wales



CARE AND MAINTENANCE INSTRUCTIONS HARLEQUIN ROCKSURE

Floor Care Best Practice

Always protect by covering newly installed floors, when other trades are operating.

Regular cleaning is more effective and will retain the performance of the product longer than if occasional 'deep clean' is adopted.

The frequency of cleaning and type of maintenance adopted is dependent on the frequency of use, the degree of soiling and the level of hygiene standard required.

Always use Harlequin recommended floor cleaning products and to the dilution rates recommended. Improper use will have an adverse effect on the floor covering, leading to both damage of the surface and potential shrinkage and staining/discolouration of the floor covering. Permanent damage cannot be reversed.

Abrasive powders/creams, strong solvents such as Acetone or highly alkaline solutions should not be used as they will do irreversible damage to the floor.

Cleaning Equipment Required

- 1) Microfibre Mops x 4
 - a) to sweep the floor.
 - b) to damp wipe the floor with the matte polish.
 - c) to mop the floor when using the Harlequin Vinyl Daily Cleaner.
 - d) to damp mop when rinsing the floor.
- 2) Harlequin Vinyl Daily floor cleaner 5 litres
- 3) Matte floor polish (any proprietary polish used for treating vinyl or wood surface)

